

SECTION 02846

SIGNAGE

1.01 SECTION INCLUDES..... 2

1.02 RELATED REQUIREMENTS 2

2.01 ACCEPTABLE MANUFACTURER..... 2

2.02 SIGNS..... 2

2.03 POSTS..... 2

SECTION 02846

SIGNAGE

PART 1 - GENERAL

1.01 SECTION INCLUDES

Provide traffic control signs complying with U.S. Department of Transportation, Federal Highway Administration's Manual "Uniform Traffic Control Devices", local codes, and as specified. See Drawings for type, location, and quantity of signs required.

1.02 RELATED REQUIREMENTS

- A. Construction Drawings.
- B. Manufacturer's Mounting Instructions.

PART 2 - PRODUCTS

2.01 ACCEPTABLE MANUFACTURER

Signs to be equivalent to those manufactured by SA-SO, Inc., Grand Prairie, TX.

2.02 SIGNS

To be painted with reflective baked-enamel finish with following colors:

- A. "STOP" Signs: (R1-1) 24"x24", Octagon, reflectorized copy and border.
- B. "SPEED LIMIT" Signs: (R2-1) 18"x24", black legend on white background.
- C. "HANDICAPPED SYMBOL" Signs: (R7-Series) 18"x24", white legend on blue background.
- D. "NO PARKING, FIRE LANE" Signs: (R7-Series) 12"x18", red letters on white background.
- E. "KEEP RIGHT" signs: (R4-7a) 18"x24", black letters and symbol on white background.
- F. "DO NOT ENTER" Signs: (R5-1) Highway Dept. standard red and white sign except 24"x24" size.
- G. Miscellaneous Signs: Per Uniform Traffic Control Device Manual Recommendations.

2.03 POSTS

Channel galvanized posts with galvanized sign-mounting hardware for each sign.

PART 3 - EXECUTION

Set sign posts vertical and plumb with bottom of sign at 5' above finish grade. Mount signs in accordance with manufacturer's instructions.

---END OF SECTION 02846---